

Tile Cleaner™

Deep Cleaning System for Commercial Hard Tile and Concrete Floors

Degree of cleaning needed	Ounces Per Gallon of Water
Moderate - office or lobby	4 ounces/gallon of water
Lobby Entry Restaurant	4-6 ounces/gallon of water
Soap build up / Dirty grout	6-8 ounces/gallon of water
Greasy Kitchen build up	8-10 ounces/gallon of water

For vinyl, wood and painted concrete surfaces; product should be used at concentration no greater than 4 ounces per gallon of water.

Tile Cleaner[™] may be used with a mop, a sprayer, a pressure washer or steam cleaner. Apply and allow to stand on the surface for 5-10 minutes. *Let the cleaner do the work!* Scrub with a deck brush or doodle bug to cut through any grease build up. Rinse with cold or hot water and squeegee to drain when possible.

EXTREME BUILD UP FOR HARD TILE SURFACES WE RECOMMEND

For the first two applications using Tile Cleaner[™] please use at a strength of 10 ounces per gallon of water to remove the excess buildup of cleaning products and to raise the COF. Leave the product on the floor for a minimum of 10-15 minutes on the first two applications making sure to keep the floor wet.

You will be able to note a distinctive difference after using Tile Cleaner™ as instructed above.